



MAGELLAN

Models: Magellan 2-AC, Magellan 2+2-AC, Magellan 4-AC, Magellan 4+2-AC

VEHICLE STANDARD FEATURES

Four year limited warranty, two year bumper-to-bumper warranty (less wear items)
Eight 6 V (48 V) batteries
5.5 hp AC motor (Magellan 2-AC, Magellan 2+2-AC)
6.7 hp AC motor (Magellan 4-AC, Magellan 4+2-AC)
275 A controller (Magellan 2-AC, Magellan 2+2-AC)
350 A controller (Magellan 4-AC, Magellan 4+2-AC)
Headlights, LED taillights, brake lights, turning signals
Folding tinted windshield
Horn and reverse beeper
LED turn signal mirrors
Speedometer, odometer, battery indicator
2-point seat belts
High/Low speed switch
Automatic battery charger
48 V to 12 V voltage reducer for accessories
Rear locking trunk (on Magellan 2-AC, Magellan 4-AC)
Easy access programming / trouble-shooting port under dash

VEHICLE OPTIONS AND UPGRADES

LSV (NEV) street legal package
Battery filling system
Black seats
On-board charger

STANDARD COLORS

	Black
	Metallic Silver
	Passion Red
	Navy Blue
	White



Magellan 2-AC



Magellan 2+2-AC



Magellan 4-AC



Magellan 4+2-AC



MAGELLAN

Vehicle Specifications

Specifications are subject to change without notification.

	Magellan 2-AC	Magellan 2+2-AC	Magellan 4-AC	Magellan 4+2-AC
DIMENSIONS				
<i>Overall dimensions</i>	94"L x 46"W x 74"H	115"L x 47"W x 75"H	126"L x 47"W x 75"H	146"L x 47"W x 75"H
<i>Wheel base</i>	68"	68"	97"	97"
<i>Ground clearance</i>	5"	5"	5.5"	5.5"
<i>Wheel type</i>	10" aluminum	10" aluminum	10" aluminum	10" aluminum
<i>Tire size</i>	205/50/10, 4-ply DOT	205/50/10, 4-ply DOT	205/50/10, 4-ply DOT	20.5x8-10, 6-ply DOT
<i>Tire pressure</i>	30 psi	30 psi	30 psi	50 psi
BODY				
<i>Body material</i>	Plastic	Plastic	Plastic	Plastic
<i>Roof</i>	Plastic (body paint match)	Extended plastic (body paint match)	Plastic (body paint match)	Extended plastic (body paint match)
POWER				
<i>Battery system</i>	8x6 V, Trojan T-105	8x6 V, Trojan T-105	8x6 V, Trojan T-105	8x6 V, Trojan T-105
<i>Motor power</i>	5.5 hp AC motor	5.5 hp AC motor	6.7 hp AC motor	6.7 hp AC motor
<i>Controller power</i>	275 A Curtis 1234-5271	275 A Curtis 1234-5271	350 A Curtis 1234E-5371	350 A Curtis 1234E-5371
PERFORMANCE				
<i>Passengers</i>	2	4	4	6
<i>Top speed</i>	19.5 mph (20-25 with LSV option)	19.5 mph (20-25 with LSV option)	19.5 mph (20-25 with LSV option)	19.5 mph (20-25 with LSV option)
<i>Top climbing grade</i>	30%	30%	30%	30%
<i>Turning radius</i>	10 ft	10 ft	15 ft	15 ft
<i>Load capacity</i>	800 lbs	800 lbs	660 lbs	1000 lbs
<i>Weight with batteries</i>	1190 lbs	1290 lbs	1323 lbs	1429 lbs
<i>Brake system</i>	Four-wheel hydraulic disc with electric-mechanical parking brake	Four-wheel hydraulic disc with electric-mechanical parking brake	Four-wheel hydraulic disc with electric-mechanical parking brake	Four-wheel hydraulic disc with electric-mechanical parking brake
<i>Drive train</i>	Direct rear drive with 12:1 ratio	Direct rear drive with 12:1 ratio	Direct rear drive with 12:1 ratio	Direct rear drive with 12:1 ratio
STEERING AND SUSPENSION				
<i>Steering system</i>	Rack and pinion	Rack and pinion	Rack and pinion	Rack and pinion
<i>Front suspension</i>	Independent A-arm, coil over shocks	Independent A-arm, coil over shocks	Independent A-arm, coil over shocks	Independent A-arm, coil over shocks
<i>Rear suspension</i>	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock