



SS LIMITED 48 V

Models: SS Limited 48-2, SS Limited 48-2+2, SS Limited 48-4, SS Limited 48-4+2

VEHICLE STANDARD FEATURES

Four year limited warranty, two year bumper-to-bumper warranty (less wear items)
Eight 6 V (48 V) batteries
5.5 hp DC motor
400 A controller
Automotive carpet for cab and bagwell
Two-tone plush color-matched seats
Chrome side rails and 12" rims
Headlights, taillights, brake lights, turning signals
Folding tinted windshield
Horn and reverse beeper
Rear view mirrors
Battery indicator
Plastic battery box
2-point seat belts
High/Low speed switch
Automatic battery charger
48 V to 12 V voltage reducer for accessories
Rear scuff guards
Locking glove box
Easy access programming / trouble-shooting port under dash



SS Limited 48-2



SS Limited 48-2+2



SS Limited 48-4



SS Limited 48-4+2

VEHICLE OPTIONS AND UPGRADES

LSV (NEV) street legal package
Battery filling system
On-board charger
Carbon fiber treatment (dashboard, steering wheel)
Wood grain treatment (dashboard, steering wheel, and seat back)
2-in-1 combo seat
Max-5 aluminum flip seat

SS LIMITED EXCLUSIVE COLORS

	Caribbean Blue		Metallic Maroon
	Electric Blue		Oyster Pearl
	Liquid Copper		Rally Red
	Metallic Black		Spirited Green
	Metallic Gray		



Ballistic Green, Jet Black



Carbon Fiber, Jet Black



Diamante Roulette Red, Jet Black



Liquid Copper, Jet Black



Metallic Blue, Vanilla



Super White, Jet Black



Vanilla, Jet Black



SS LIMITED 48 V

Vehicle Specifications

Specifications are subject to change without notification.

	SS Limited 48-2	SS Limited 48-2+2	SS Limited 48-4	SS Limited 48-4+2
DIMENSIONS				
<i>Overall dimensions</i>	94"L x 47"W x 72"H	115"L x 47"W x 77"H	123"L x 47"W x 77"H	144"L x 47"W x 77"H
<i>Wheel base</i>	67"	67"	96"	96"
<i>Ground clearance</i>	5"	5"	5"	5"
<i>Wheel type</i>	12" Dura Chrome	12" Dura Chrome	12" Dura Chrome	12" Dura Chrome
<i>Tire size</i>	20x9.0-12, 4-ply DOT	20x9.0-12, 4-ply DOT	215/50-12, 4-ply DOT	215/50-12, 4-ply DOT
<i>Tire pressure</i>	22 psi	22 psi	30 psi	30 psi
BODY				
<i>Body material</i>	Plastic	Plastic	Plastic	Plastic
<i>Roof</i>	Plastic (body paint match)	Extended plastic (body paint match)	Plastic (body paint match)	Extended plastic (body paint match)
<i>Side rails</i>	Chrome	Chrome	Chrome	Chrome
POWER				
<i>Battery system</i>	8x6 V, Trojan T-105	8x6 V, Trojan T-105	8x6 V, Trojan T-105	8x6 V, Trojan T-105
<i>Motor power</i>	5.5 hp Continuous DC	5.5 hp Continuous DC	5.5 hp Continuous DC	5.5 hp Continuous DC
<i>Controller power</i>	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking
PERFORMANCE				
<i>Passengers</i>	2	4	4	6
<i>Top speed</i>	19.5 mph (20-25 with LSV option)	19.5 mph (20-25 with LSV option)	19.5 mph (20-25 with LSV option); speedometer included	19.5 mph (20-25 with LSV option); speedometer included
<i>Top climbing grade</i>	25%	20%	20%	20%
<i>Turning radius</i>	10 ft	10 ft	12 ft	12 ft
<i>Load capacity</i>	600 lbs	660 lbs	660 lbs	1000 lbs
<i>Weight with batteries</i>	1200 lbs	1370 lbs	1430 lbs	1570 lbs
<i>Brake system</i>	Rear drum	Rear drum	Four-wheel hydraulic drum brakes with hand-activated parking brake	Four-wheel hydraulic drum brakes with hand-activated parking brake
<i>Drive train</i>	Direct rear drive with 10.25:1 ratio	Direct rear drive with 10.25:1 ratio	Direct rear drive with 10.25:1 ratio	Direct rear drive with 10.25:1 ratio
STEERING AND SUSPENSION				
<i>Steering system</i>	Rack and pinion	Rack and pinion	Rack and pinion	Rack and pinion
<i>Front suspension</i>	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock
<i>Rear suspension</i>	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock