



# SS LIMITED SPORT

Models: SS Limited Sport 2+2, SS Limited Sport 4+2

VEHICLE STANDARD FEATURES
Four year limited warranty, two year bumper-to-bumper warranty (less wear items)
Eight 6 V (48 V) batteries
5.5 hp DC motor, 400 A controller
Automotive carpet for cab
Two-tone plush color-matched seats
Chrome side rails and 12" rims
Brush guard and fender flares
Clay basket (standard on SS Limited Sport 2+2 only)
Headlights, taillights, brake lights, turning signals
Folding tinted windshield
Horn and reverse beeper
Rear view mirrors
Battery indicator, automatic battery charger
2-point seat belts
High/Low speed switch
Locking glove box
48 V to 12 V voltage reducer for accessories
Easy access programming / trouble-shooting port under dash



SS Limited Sport 2+2



SS Limited Sport 4+2

VEHICLE OPTIONS AND UPGRADES
LSV (NEV) street legal package
Extended roof (on Sport 2+2; standard on Sport 4+2)
Clay basket (on Sport 4+2; standard on Sport 2+2)
Battery filling system
On-board charger
Carbon fiber treatment (dashboard, steering wheel)
Wood grain treatment (dashboard, steering wheel, and seat back)
2-in-1 combo seat
Max-5 aluminum flip seat

SS LIMITED EXCLUSIVE COLORS			
	Caribbean Blue		Metallic Maroon
	Electric Blue		Oyster Pearl
	Liquid Copper		Rally Red
	Metallic Black		Spirited Green
	Metallic Gray		



Ballistic Green, Jet Black



Carbon Fiber, Jet Black



Diamante Roulette Red, Jet Black



Liquid Copper, Jet Black



Metallic Blue, Vanilla



Super White, Jet Black



Vanilla, Jet Black



# SS LIMITED SPORT

## Vehicle Specifications

Specifications are subject to change without notification.

	SS Limited Sport 2+2	SS Limited Sport 4+2
<b>DIMENSIONS</b>		
<i>Overall dimensions</i>	116"L x 52"W x 78"H (295 cm x 208 cm x 198 cm)	138"L x 52"W x 78"H (351 cm x 208 cm x 198 cm)
<i>Wheel base</i>	68" (173 cm)	96" (244 cm)
<i>Ground clearance</i>	7" (17.8 cm)	7" (17.8 cm)
<i>Wheel type</i>	12" (30.5 cm) Dura Chrome	12" (30.5 cm) Dura Chrome
<i>Tire size</i>	23 x 10.5 x12, 4-ply DOT	23 x 10.5 x12, 4-ply DOT
<i>Tire pressure</i>	15 psi (103 kPa)	15 psi (103 kPa)
<b>BODY &amp; CHASSIS</b>		
<i>Chassis</i>	Steel	Steel
<i>Body material</i>	Plastic	Plastic
<i>Roof</i>	Plastic (body paint match)	Extended plastic (body paint match)
<i>Side rails</i>	Chrome	Chrome
<b>POWER</b>		
<i>Battery system</i>	8x6 V, Trojan T-105	8x6 V, Trojan T-105
<i>Motor power</i>	5.5 hp (4.1 kW) Continuous DC	5.5 hp (4.1 kW) Continuous DC
<i>Controller power</i>	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking
<b>PERFORMANCE</b>		
<i>Passengers</i>	4	6
<i>Top speed</i>	17 mph, 21.9 mph minimum with LSV option (27.4 kph, 35.2 kph minimum with LSV option)	17 mph, 21.9 mph minimum with LSV option (27.4 kph, 35.2 kph minimum with LSV option)
<i>Top climbing grade</i>	28%	28%
<i>Turning radius</i>	10 ft (3 m)	13 ft (4 m)
<i>Load capacity</i>	600 lbs (272 kg)	900 lbs (408 kg)
<i>Weight with batteries</i>	1430 lbs (649 kg)	1650 lbs (748 kg)
<i>Brake system</i>	Rear drum	Four-wheel hydraulic drum brakes with hand-activated parking brake
<i>Drive train</i>	Direct rear drive with 12:1 ratio	Direct rear drive with 12:1 ratio
<b>STEERING AND SUSPENSION</b>		
<i>Steering system</i>	Rack and pinion	Rack and pinion
<i>Front suspension</i>	Leaf spring and shock	Leaf spring and shock
<i>Rear suspension</i>	Leaf spring and shock	Leaf spring and shock