



SPORT

Models: Sport 2+2, Sport 4+2

VEHICLE STANDARD FEATURES

Four year limited warranty, two year bumper-to-bumper warranty (less wear items)
Eight 6 V (48 V) batteries
5.5 hp DC motor
400 A controller
Brush guard and fender flares
Clay basket (standard on Sport 2+2 only)
Headlights, taillights, brake lights, turning signals
Folding tinted windshield
Horn and reverse beeper
Rear view mirrors
Battery indicator, automatic battery charger
Plastic battery box
2-point seat belts
High/Low speed switch
48 V to 12 V voltage reducer for accessories
Easy access programming / trouble-shooting port under dash



Sport 2+2

VEHICLE OPTIONS AND UPGRADES

LSV (NEV) street legal package
Extended roof (on Sport 2+2; standard on Sport 4+2)
Clay basket (on Sport 4+2; standard on Sport 2+2)
Roof rack
Locking glove box
Black seats
3-point seat belts
On-board charger
Carbon fiber treatment (dashboard and steering wheel)
Wood grain treatment (dashboard, steering wheel, and seat back)
Max-5 aluminum flip seat
SS Limited upgrade



Sport 4+2

STANDARD COLORS		PREMIUM COLORS	
	Black		Almond Pearl
	Red		Metallic Green
	Navy Blue		Metallic Silver
	White		Yellow
			True Timber® Camouflage



SPORT

Vehicle Specifications

Specifications are subject to change without notification.

	Sport 2+2	Sport 4+2
DIMENSIONS		
<i>Overall dimensions</i>	116"L x 52"W x 78"H (295 cm x 208 cm x 198 cm)	138"L x 52"W x 78"H (351 cm x 208 cm x 198 cm)
<i>Wheel base</i>	68" (173 cm)	96" (244 cm)
<i>Ground clearance</i>	7" (18 cm)	7" (18 cm)
<i>Wheel type</i>	12" aluminum (30.5 cm)	12" aluminum (30.5 cm)
<i>Tire size</i>	23 x 10.5 x12, 4-ply DOT	23 x 10.5 x12, 4-ply DOT
<i>Tire pressure</i>	15 psi (103 kPa)	15 psi (103 kPa)
BODY & CHASSIS		
<i>Chassis</i>	Steel	Steel
<i>Body material</i>	Plastic	Plastic
<i>Roof</i>	Fiberglass (body paint match)	Extended plastic (body paint match)
<i>Side rails</i>	Aluminum	Aluminum
POWER		
<i>Battery system</i>	8x6 V, Trojan T-105	8x6 V, Trojan T-105
<i>Motor power</i>	5.5 hp (4.1 kW) Continuous DC	5.5 hp (4.1 kW) Continuous DC
<i>Controller power</i>	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking
PERFORMANCE		
<i>Passengers</i>	4	6
<i>Top speed</i>	17 mph, 21.9 mph minimum with LSV option (27.4 kph, 35.2 kph minimum with LSV option)	17 mph, 21.9 mph minimum with LSV option (27.4 kph, 35.2 kph minimum with LSV option)
<i>Top climbing grade</i>	28%	28%
<i>Turning radius</i>	10 ft (3 m)	13 ft (4 m)
<i>Load capacity</i>	600 lbs (272 kg)	900 lbs (408 kg)
<i>Weight with batteries</i>	1430 lbs (649 kg)	1650 lbs (748 kg)
<i>Brake system</i>	Rear drum	Four-wheel hydraulic drum brakes with hand-activated parking brake
<i>Drive train</i>	Direct rear drive with 12:1 ratio	Direct rear drive with 12:1 ratio
STEERING AND SUSPENSION		
<i>Steering system</i>	Rack and pinion	Rack and pinion
<i>Front suspension</i>	Leaf spring and shock	Leaf spring and shock
<i>Rear suspension</i>	Leaf spring and shock	Leaf spring and shock